

RE-HEALING™ RF6, 6% FOAM CONCENTRATE

CONCENTRATES



Description

RE-HEALING™ RF6 foam concentrate from SOLBERG® is an innovative environmentally sustainable fluorosurfactant and fluoropolymer-free foam concentrate used to effectively extinguish Class B hydrocarbon fuel fires. Proportioned at 6% solution, RE-HEALING RF6 foam concentrate can be used in fresh, salt or brackish water. RE-HEALING RF6 foam concentrate possesses excellent burn back resistance due to its remarkable flow and rapid resealing characteristics. RE-HEALING foam concentrates are formulated using a new high performance synthetic foam technology to replace traditional AFFF and AR-AFFF foam concentrates and older fluoroprotein foams.

Application

RE-HEALING RF6 foam concentrate is intended for use on Class B hydrocarbon fuel fires. It is not intended for use on Class B polar solvent fuels. The foam concentrate can be used to prevent re-ignition of a liquid spill and control hazardous odors. On Class A fuels, RE-HEALING RF6 foam concentrate will improve extinguishment in deep-seated fires.

Foam non-air aspirating discharge devices as well as air aspirating discharge devices, including standard sprinkler heads, can be used to obtain maximum results. The product is mixed 6 parts foam concentrate to 94 parts water. It may also be used as a 6% pre-mix solution. RE-HEALING RF6 foam concentrate is compatible with most dry powder (chemical) agents, and provides even greater fire protection against three-dimensional fires.

Performance


Fire Performance

RE-HEALING RF6 foam concentrate has been tested against Underwriters Laboratories, Inc. (UL) Standard 162 (latest edition).

Foam Proportioning

RE-HEALING RF6 foam concentrate can be proportioned at the proper foam solution percentage using common foam proportioning devices such as:

- Eductors
- Inline balanced pressure proportioners
- Ratio controllers
- Self-educting nozzles



SOLBERG

Typical Physical Properties at 77°F (25°C)

Appearance:	Brown liquid
Freezing Point:	23° F (-5° C) <i>(No quality loss after thawing)</i>
Maximum storage temp:	<120° F (49° C)
pH:	7.02
Refractive index:	1.3715
Specific gravity:	1.063
Surface tension:	26.5 mN/n
Viscosity:	5100 cps

Storage

The minimum and maximum temperature for RE-HEALING RF6 foam concentrate is 35° F to 120° F (1.7° C to 49° C).

When stored in original containers or in manufacturer recommended equipment and within the specified temperature range, the shelf life is a minimum of 10 years.

Compatibility

RE-HEALING RF6 foam concentrate should not be mixed with other foam concentrates. For questions about compatibility or mixing, consult Solberg Technical Services.

Solberg is a global company that is a one-stop resource for firefighting foam concentrates and custom-designed foam suppression systems hardware, offering both traditional and innovative firefighting foam technology. www.solbergfoam.com

**Materials of Construction Compatibility**

RE-HEALING RF6 foam concentrate is compatible with multiple materials of construction such as carbon steel, stainless steel, brass, polyethylene and PVC. Galvanized steel should not be used in direct contact with the foam concentrate. For questions about materials of construction compatibility, consult Solberg Technical Services.

Inspection

RE-HEALING RF6 foam concentrate or pre-mix solution should be inspected annually per National

Fire Protection Association (NFPA) Standards 11 and 25. A sample of the foam concentrate should be sent to the manufacturer for quality conditioning testing in accordance to NFPA 11.

Environmental Information

RE-HEALING foam concentrates are fluorosurfactant, fluoropolymer-free products for use on Class B hydrocarbon fuels with no environmental concerns for persistence, bioaccumulation or toxic break down.

Approvals & Listings

SOLBERG manufactured products are thoroughly inspected and undergo rigorous quality control tests. These evaluations analyze the foam's physical parameters as well as the finished product's fire performance. A Certificate of Analysis (CoA) is issued with every batch.

RE-HEALING RF6 foam concentrate has been tested against Underwriters Laboratories, Inc. (UL) Standard 162.

Ordering Information

RE-HEALING RF6 foam concentrate is available in pails, drums, totes and bulk quantities.

PART NO.	DESCRIPTION	SHIPPING WEIGHT	CUBE
20040	RE-HEALING RF6, 5 gallon (20 litre) pail	45 lb (21 kg)	1.25 ft ³ (0.04 m ³)
20041	RE-HEALING RF6, 55 gallon (200 litre) drum	495 lb (224 kg)	11.83 ft ³ (0.33 m ³)
20042	RE-HEALING RF6, 265 gallon (1000 litre) tote	2465 lb (1118 kg)	50.05 ft ³ (1.42 m ³)
20043	RE-HEALING RF6, bulk	Call Customer Services	